

AGGRESSOR WATERCRAFTS TYPHOON



ALEXIS FIRE EQUIPMENT DEMO / SERIES 2316

TECHNICAL SPECS

HULL AND DECK FEATURES:

- Aluminum hull 26' L x 84" W x 36" 16 degree V
- 6" hardchimes
- 100" beam
- 3/16" thick marine alloy aluminum sides and bottom
- Reinforced bottom with ribs of 2" x 2" x 1/8" tubing set on 12" centers
- Side ribs 2" x 4" x 1/8"
- Additional foam floatation installed in the sides, under flooring and within the front deck
- Hull is approximately 5000 pounds
- Heavy duty flexible black bumper with tube insert covers all hardware
- Bumper runs a full 26' on each side, from transom to bow

SIDE SPLASH RAILS:

- 1-1/2" x 2" x 1/8" thick angle
- Disperses the water out and away from the boat

DUAL ENGINE MOTOR GUARD:

- Dual engine motor guard mounted along the transom and runs from side to side
- Curved 1-1/2" pipe provides a safety guide

DIVE DOOR:

- Aluminum dive door with 24" opening is located on starboard, right-hand side and sealed with rubber gaskets

CLEATS:

- Four 10" Aluminum Attwood cleats welded onto the gunwale rim
- Cleat accepts rope up to 5/8" in diameter

ANCHOR:

- D-L Sentinel 40 lbs. fluke design anchor
- 1/2" galvanized steel shackle and 200' of 1/2" rope included. (Unicord rope is twisted nylon anchor line – tensile strength of 3340 lbs.)

DOCK LINE:

- Three 25' and one 50' Unicord line
- Red and white polypropylene 8 strand hollow braid lines

TOOL BRACKETS:

- Aluminum tool brackets to secure loose equipment
- Customizable depending upon needs and tools of each department
- Permanently welded or bolted to the hull

ENGINE AND FUEL SYSTEM:

- One ME225XL and one ME225CXL Mercury outboard engine
- Stainless steel props
- Shift control rigging
- Four shift cables
- One extension harness
- Dual engine synchronizer
- Dual engine tie bar kit
- Ignition choke assembly
- Dual lanyard stop switch

FUEL SYSTEM

- 120 gallon capacity
- Dual 60 gallon fuel tanks USCG Approved
- Seamless one piece polyethylene construction
- Includes permanent hold down kit, fuel line assembly and an aluminum battery tray
- Installation kit includes a 1-1/2" diameter fill hose with deck fill, vent, and clamps
- Standard plumbing to the outboard engines and the pumping system

AGGRESSOR
WATERCRAFTS

ALEXIS FIRE EQUIPMENT 109 East Broadway, Alexis, Illinois 61412

TECHNICAL SPECS [CONTINUED]

PUMPING SYSTEM:

MAIN FIRE SUPPRESSION PUMP

- Darley Portable Hercules HE64PR
- Constructed of aluminum alloy anodized for superior corrosion resistance
- High strength bronze alloy impeller double hubbed to balance hydraulic thrust
- Tax 2-cylinder/2-cycle engine liquid cooled
- Rotary vane belt driven primer
- Alternator charges boat battery while pumping
- Readout panel: Pressure gauge, throttle control, kill switch and light
- Fuel supply interconnects with boat main fuel supply
- Keyless electronic ignition switch, throttle, thermal relief valve
- Mounted on a skid frame base for maximum strength
- Insulated enclosure protected by aluminum treadplate with air scoops for circulation
- Plumbing includes 4" suction and removable screen system
- Suction from under the boat
- 25-1/2"H x 34"L x 29-3/4"
- Approximately 225 lbs. dry

BILGE PUMP

- Two 1500 GPH bilge pumps
- Silent and no vibration
- Floatable and automatic switch, activates on contact with water
- ON/OFF manual toggle switch mounted to the dash.

LIGHTING & ELECTRICAL:

EMERGENCY LIGHTS AND SIREN

- Code-3 36" LED lightbar
- Code-3 Model 3672L4 siren and CP100 siren speaker mounted on front deck of the boat
- Master switch installed for emergency lighting

NAVIGATION LIGHTS

- Two Attwood stowaway bow lights, poles, and pole bases
- Bow light is a one-mile combination sidelight - OAH 10"

WORK LIGHTS

- Four 12V work lights, two aft and two fore
- Work lights are 3,000 candlepower sealed beam lights

REMOTE SEARCHLIGHT

- Jabsco 6" sealed beam, 200,000 candle power searchlight
- Remote controlled and has a chrome brass housing and base

MARINE BATTERY SYSTEM

- Two 12V Marine crank batteries
- Battery case
- Strap down kit and aluminum battery tray
- Perko battery selector switch allows for selection between dual batteries for starting, charging or operation of both batteries in parallel
- Switch also allows addition of an extra battery
- Continuous 250 amp capacity and 360 amp intermittent
- 110 volt Charlie 40 amp automatic charger and battery conditioner
- One 125V shoreline manual connection (mating drop cord connector supplied)
- One 50 Amp 125V Female HUB-503NM recessed male plug and cover installed in the boat cabin
- One female HUB-63CM60 will be furnished with the unit

MONITOR & PLUMBING:

- 750 GPM Stang monitor with 500 GPM nozzle
- Stainless steel plumbing
- 650 GPM pump
- Rear 2" attack line

TRAILER FEATURES:

- 26' tandem axle trailer
- Lights, winch, coupler, carpeted rails and side bunks, EZ lube axles, tongue jack and stand, 14" wheels, all standard
- Steel channel construction
- Electric brakes installed tandem axles
- Spare tire and mounting bracket

COCKPIT FEATURES:

- Marine aluminum construction
- Enclosed on three sides with rear access open
- Location allows for a walkway on each side of the boat
- Built-in console shelf underneath instrumentation panel, overhead storage shelf
- Console instrumentation includes: Two tachometers, speedometer, two trim systems, two hour meters, two voltmeters, one depth finder, two fuel tank gauges, one 12V accessory plug
- Dual wiper system
- Dual 12V personal fans
- Hydraulic steering system with steering wheel
- 78"H x 54"W – 6'x6" headroom

FIRST AID KIT

- Healer product medical first aid kit fulfills NFPA requirements for a boat
- Contains adhesive strips, gauze bandages, gauze pads, adhesive tape, motion sickness pills, sting relief swabs, wound wipes, first aid/burn cream, sunscreen, towellette, aspirin, scissors, bandages, and ointments

NAVIGATION COMPASS

- Aqua Meter Illuminated compasses
- Mounted on the dash or instrument panel
- Adjustable dome
- Illuminated for nighttime operation

MARINE BRAND RADIO SYSTEM

- Uniden Mini VHF 2-Way Marine Radio
- 90 channel VHF fixed radio
- Program scan, backlit keypad and LCD readout, instant on, 16 or 9 push button channel select, weather alert, weather scan, public address access, 25W/1W power, microphone with channel select, and external speaker jack

ANTENNA

- Shakespeare antenna
- 3' tall / 6dB performance gain
- Stainless steel whip
- Die cast zinc mirror finish bracket

ELECTRIC HORN

- Marinco/AFI twin electric horn
- Stainless steel covers, diaphragms, and mounting bracket
- Combines dual high and low tones

DIGITAL DEPTH FINDER:

- Maximum depth readout of 199 feet
- White face and bezel has a backlit display for night operations.
- Adjustable alarm and a transom/inside-hull mounted transducer

