## COMMERCIAL TOP CONTROL PUMPER



## AMANA BENEFITED FIRE DISTRICT AMANA, IOWA

ЗĿ,

## **TECHNICAL SPECS**

- Freightliner M2 4-Door Chassis ٠
- Cummins ISC-330, 330-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- Heavy Duty 3/16" Aluminum Body
- 1750-Gallon Poly Tank •
- One (1) 2 ½" Tank fill, rear
- One (1) Newton 10" square manual dump with 36" extension
- Hale DSD 150, 1500-GPM Pump •
- Top Control Pump operator's panel with heated pump ٠ enclosure
- Four (4) 2 1/2" Discharges, one (1) left side, two (2) right side and one (1) rear
- Two (2) 3" Discharges, one (1) left side and one (1) over pump for deck gun
- Two (2) 2 ½" gated suction, one (1) each side
- One (1) 5" Suction, rear
- Two (2) 1 1/2" Cartridge lay Preconnects with capacity for 200-ft of hose each
- Four (4) Dual Air bottle compartments, two (2) each side wheel wells
- **ROM Roll Up Doors**
- Two (2) Suction hose storage compartments with rear • access
- Ladder and pike pole brackets, right side compartment top
- Kussmaul 1200 battery charger with Viair Air compressor
- Kussmaul Super Auto Eject 120-volt shoreline
- Class 1 Total System Manager for electrical load ٠ management
- Code 3 Electronic Siren with 100-watt Federal speaker
- Three (3) Whelen Scene lights, one (1) each side and one ٠ (1) rear
- Two (2) Unity Deck lights, rear
- Two (2) Extenda Lite 12-volt 150-watt telescopic lights, one (1) each side
- One (1) 120-volt power strip shoreline powered Whelen LED Warning Light Package
- •
- 9'9" Overall height 33' 9" Overall length 278" Wheelbase

165.2" Cab to Axle

•

- 16,000 FAWR
  - 31,000 RAWR
    - 47,000 GVWR



Alexis Fire Equipment 109 East Broadway Alexis, Illinois 61412

We would like to thank the

Amana Benefited Fire District







To view more photos of this unit, visit us on the web at www.AlexisFire.com.



for their business.