MINI PUMPER







CITY OF BELLEVUE FIRE DEPARTMENT BELLEVUE, IOWA

TECHNICAL SPECS

- Ford F-550XL 4-Door 4x4 DRW Chassis
- Powerstroke 6.7L V-8, 300-HP Diesel Engine
- TorqShift Automatic Transmission
- Heavy Duty 3/16" Aluminum Body
- ROM painted Roll Up Doors
- · Luverne stainless steel nerf bars
- Warn stainless steel brush guard with wrap around and receiver
- Reese type hitch/winch receiver with electrical connections, rear
- 250-Gallon Poly Tank with 12-Gallon foam tank
- Hale DSD 1250-GPM Pump
- · Left side pump operator's panel
- Two (2) 2 1/2" Discharges, left side
- One (1) 3" Discharge, right side
- One (1) 2 1/2" Gated Suction, left side
- Two (2) Mattydale Preconnects, one (1) 2 ½" and one (1) 1 ½", across top
- Foam Pro Turbo Stream Ultra-High Pressure Foam System
- Three (3) Air bottle compartments, Two (2) right and one (1) left side
- Three (3) Walk-away Air pack brackets, right side compartment
- Multi use storage compartment right side hose bed

- Turtle Tile on shelves and/or trays of compartments
- Progressive Dynamics on-board battery charger with Viair Air compressor
- Kussmaul Super Auto Eject 120-volt shoreline connection
- Floor mounted console for emergency switches with map/binder storage, cab
- Code 3 Electronic Siren with 100-watt Whelen speaker
- Six (6) Weldon Scene lights, two (2) each side and two (2) rear
- Two (2) Akron Extenda-Lite 12-volt 220-watt telescopic lights, one (1) each side
- Weldon LED Warning Light Package
- 7' 8" Overall height
- 26' 9" Overall length
- 200" Wheelbase
- 84" Cab to Axle
- 7,000 FAWR
- 14,700 RAWR
- 19,500 GVWR





To view more photos, visit www.AlexisFire.com

WE WOULD LIKE TO THANK THE CITY OF BELLEVUE FIRE DEPARTMENT FOR THEIR BUSINESS.



