

REAR MOUNT PUMPER



CATERPILLAR, INC. MOSSVILLE, ILLINOIS

TECHNICAL SPECS

- Peterbilt 340 2-Door Chassis
- Caterpillar C7 330-HP Diesel Engine
- Allison 3000 EVS-P Automatic Transmission
- Heavy Duty 3/16" Aluminum Body
- UPF 750-Gallon Poly Tank
- Hale PSD1000-GPM PTO Pump
- Five (5) 2 1/2" Discharges, rear
- One (1) 2 1/2" Gated rear suction
- One (1) 3" Discharge for Deck Gun, right side rear hosebed over pump
- One (1) Elkhart Stinger Deck Gun with Elkhart master Stream nozzle and TFT extend-a gun
- Three (3) 1 1/2" Preconnects, One (1) front bumper and two (2) right side hosebed
- Left side rear pump operator's panel
- 16" Front Bumper Extension with center hosewell
- Four (4) Air bottle compartments, two (2) each side
- ROM Roll Up Doors with locks
- Three (3) Vertical Pull out boards, one (1) left side and two (2) right side
- Two (2) FlameFighter walk-away air Pak brackets, right side on pull out board
- One (1) Zico Quic Index SCBA bracket on roll out tray, right side rear
- Four (4) Pike pole tubes, two (2) each side compartment top
- Floor mounted console for emergency switches, cab
- Class 1 Total system manager electrical load management
- Code 3 Electronic Siren with 100-watt Federal speaker
- One (1) Optronics 170-watt hand held spot light, cab
- One (1) Orange Streamlight Firebox vehicle mount system
- Two (2) 12-volt Extenda-Lite HID 150-watt telescopic lights, one (1) each side
- Power Arc Warning Light Package
- 9' 7" Overall height
- 23' 8" Overall length
- 150" Wheelbase
- 80.2" Cab to Axle
- 12,000 FAWR
- 22,700 RAWR
- 34,700 GVWR



To view more photos of this unit, visit us on the web at www.AlexisFire.com.

We would like to thank Caterpillar Inc. for their business.



Alexis Fire Equipment
109 East Broadway
Alexis, Illinois 61412

