



FIRE SUPPRESSION UNITS / TECHNICAL SPECS

OPTIONS:

- 75 Gallon Poly Tank
- 2 1/2" Tank Valve
- Seat belts for all seating positions.
- Smooth aluminum cab doors with sliding windows (requires the canopy and soft sided cab enclosure options from Cub Cadet)
- Code 3 3692L4 Siren with 100-Watt Speaker mounted in the brush guard of the unit
- Code 3 LED warning lights – two (2) front, two (2) rear, and one (1) each side
- PowerArc PP2 warning lights – two (2) front, two (2) rear and one (1) each side

DISCHARGE OPTIONS:

- 1" Discharge
- 1 1/2" Discharge
- 1" Booster reel manual rewind with 100' of 3/4" hose

FOAM SYSTEM OPTION:

- Elkhart 241-30 30 GPM Foam Eductor

ADDITIONAL OPTIONS:

- Stokes basket storage on top of tank

PUMPING SYSTEM OPTIONS:

Darley AK 283 Pump

One (1) Darley AK 283 5.5 HP Honda OHV with recoil start. *Pump Ratings:*

- 95 GPM @ 39 PSI
- 60 GPM @ 70 PSI
- 20 GPM @ 90 PSI

Darley AK 282 Pump

One (1) Darley AK 282 9.0 HP Briggs and Stratton OHV Vanguard with electric start and manual recoil backup.

Pump Ratings:

- 120 GPM @ 36 PSI
- 95 GPM @ 83 PSI
- 60 GPM @ 118 PSI
- 20 GPM @ 144 PSI

Darley AK 290 Pump

One (1) Darley AK 290 5.5 HP Honda OHV with recoil start. *Pump Ratings:*

- 65 GPM @ 48 PSI
- 50 GPM @ 81 PSI
- 20 GPM @ 131 PSI

Darley AK 291 Pump

One (1) Darley AK 291 13 HP Briggs and Stratton OHV Vanguard with electric start and manual recoil back-up.

Pump Ratings:

- 120 GPM @ 40 PSI
- 95 GPM @ 108 PSI
- 60 GPM @ 133 PSI
- 20 GPM @ 146 PSI



Alexis Fire Equipment Company
109 East Broadway
Alexis, Illinois 61412