



FULTON FIRE PROTECTION DISTRICT FULTON, ILLINOIS

TECHNICAL SPECS

- Spartan Gladiator Evolution LFD 10" R.R.
- Cummins ISL400 - 400 HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- Heavy Duty 3/16" Aluminum Body
- 750 Gallon UPF Poly Tank IIE
- 20 Gallon Foam Cell mounted in pump module
- EZ-Fill foam tank system
- One (1) Cascade bottle behind rear body panel on each side
- Waterous CSU 1500 G.P.M. Stainless Steel Midship Pump
- Top Mount Control Panel
- Soft suction well on each side
- Hinged Pump Panels for Easy Access
- Two 1-1/2" Cartridge Lay Preconnects ahead of the pump
- One (1) 2 1/2" tank fill above rear compartment
- Two (2) 2 1/2" discharges above rear compartment
- Three (3) dual air bottle compartments in wheel wells
- High side compartments each side
- 10kw ONAN Hydraulic Generator
- Two (2) Extenda-Lite 1500 watt Lift Lights in pump module
- Two (2) Large Extenda-Lite flood lights recess mounted each side
- Two (2) large Whelen 90E000ZR scene lights mounted on the rear
- Two (2) Unity 6" 5000 candle power rear deck lights
- Hydraulic ladder rack on right side of apparatus
- Suction hose storage above left side compartments
- Suction hose storage for One (1) 10' section on hydraulic ladder rack
- Pike Pole storage on ladder rack
- Whelen Warning Light package
- Whelen FN72QLED LED Lightbar
- Whelen TAL85 LED Arrow Stick
- Class-1 "Krystal-Lite" Compartment lighting
- 9'-8" Overall Height
- 35'-3" Overall Length
- 225" Wheelbase
- 157.5" Cab to Axle
- 20,000 FAWR
- 27,000 RAWR
- 47,000 GVWR



To view more photos of this unit, visit us on the web at www.alexisfire.com

We would like to thank the Fulton Fire Protection District for their business.

Alexis Fire Equipment Company
109 East Broadway
Alexis, Illinois 61412

