FLATBED BRUSH TRUCK



KNOXVILLE COMMUNITY FIRE PROTECTION DISTRICT KNOXVILLE, ILLINOIS

TECHNICAL SPECS

- Ford F-550 XL 4-Door Chassis
- Triton 6.8L V-10, 362-HP Gasoline Engine
- Ford TorgShift Automatic Transmission
- Heavy Duty 3/16" Aluminum Body
- Luverne Stainless Steel nerf bars
- Warn Stainless Steel brush guard with wrap around and front winch receiver
- Reese type rear trailer hitch/winch receiver
- One (1) Ramsey QM 9000, 9000-lb winch
- 300-Gallon Poly booster skid Tank with 10-gallon foam tank
- Waterous PB18-3030C Pump with 18-HP Briggs & Stratton gasoline engine
- One (1) 2 1/2" Discharge, rear
- One (1) 1 1⁄2" Preconnect, left side rear compartment
- Two (2) 1" Booster lines with 10-ft of 1" hose each, front of body
- Two (2) Electrically controlled Spray booms, one (1) each side front bumper
- One (1) Hannay electric booster reel with 150-ft of 1" hose
- One (1) 2 1/2" Gated Suction, rear
- Scotty Around the Pump foam inductor/ mixer
- Two (2) compartments with two (2) drop down doors each, one (1) each side

- Two (2) Suction hose storage compartments one (1) over each side with rear access
- Stokes Basket/Ice sled storage compartment behind headache rack
- Three (3) walk-away air pack brackets, right side compartment
- Floor mounted console for emergency switches with map/binder storage, cab
- Kussmaul Auto charge 1200 battery charger
- Kussmaul Super Auto eject 120-volt shoreline
- Code-3 Electronic Siren with 100-watt Federal speaker
- Three (3) Federal GHSCENE lights, two (2) rear and one (1) pump area
- Two (2) Akron Extenda-Lite 12-volt 150-watt telescopic lights, one (1) each side
- Weldon LED Warning Light Package
- · Chevron pattern striping, rear
- 7' 8" Overall height
- 23' Overall length
- 176.2" Wheelbase
- 60" Cab to Axle
- 7,000 FAWR
- 14,706 RAWR
- 19,500 GVWR





To view more photos, visit **www.AlexisFire.com**

We would like to thank the Knoxville Community Fire Protection District for their business.

