

TOP CONTROL PUMPER



MENOMINEE-DUNLEITH FIRE PROTECTION DISTRICT EAST DUBUQUE, ILLINOIS

TECHNICAL SPECS

- International 4400 2-Door Customer supplied Chassis
- MaxxForce 9, 330-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- Heavy Duty 3/16" Aluminum Body
- ROM brand painted Roll Up Doors
- 1000-Gallon Poly Tank with 20-Gallon foam tank
- Hale QMAX-XS 1250-GPM Pump
- Pump operator's panel across top of body
- Three (3) 2 1/2" Discharges, one (1) left side and two (2) rear
- One (1) 3" Discharge, right side
- Three (3) Mattydale Preconnects, two (2) 1 1/2" and one 2 1/2", top of body
- One (1) Hannay Booster Reel with 150-ft of 1" hose, upper rear
- One (1) 2 1/2" Gated Suction, left side
- Foam Pro 1600 Foam System
- Four (4) Dual bottle Air bottle compartments, two (2) each side
- Turtle Tile on floors and/or shelves and trays of compartments
- Ladder/Suction hose storage compartment with rear access, right side
- Pike pole storage compartment with rear access, right side
- Vanner on-board battery charger
- Kussmaul Super Auto Eject 120-volt shoreline
- Kussmaul Air Auto Eject
- Dash mounted console for emergency switches
- Audiovox back-up Camera with 7" color monitor
- Two (2) Air Horns, one (1) each side of hood
- Code 3 Electronic Siren with Cast Products speaker
- Five (5) Whelen LED scene lights, two (2) each side and one (1) rear
- Two (2) Extenda-Lite 12-volt 220-watt LED telescopic lights, one (1) each side
- Whelen LED Warning Light Package
- Chevron pattern striping, rear
- 8' 10" Overall height
- 29' 10" Overall length
- 226" Wheelbase
- 158.9" Cab to Axle
- 14,000 FAWR
- 26,000 RAWR
- 40,000 GVWR



To view more photos,
visit www.AlexisFire.com

WE WOULD LIKE TO THANK
THE MENOMINEE-DUNLEITH FIRE
PROTECTION DISTRICT FOR THEIR
BUSINESS.



