COMMERCIAL TOP MOUNT PUMPER



OSCO COMMUNITY FIRE PROTECTION DISTRICT OSCO, ILLINOIS

TECHNICAL SPECS

- Freightliner M2 106, 2-Door Chassis
- Cummins ISC-330, 330-HP Diesel Engine Allison 3000 EVS Automatic Transmission
- Heavy Duty 3/16" Aluminum Body
- ROM Roll Up Doors
- 1000-Gallon Poly Tank
- One (1) 2 1/2" Firemen's Friend Tank fill, rear
- Waterous CXVC10, 1250-GPM Pump
- Top mount operator's panel
- Four (4) 2 1/2" Discharges, two (2) left side, one (1) right side and one (1) rear
- One (1) 3" Discharge over pump for deck gun Two (2) 1 ½" Speed lay Preconnects, front of apparatus
- One (1) 2 1/2" Gated Suction, left side
- Two (2) Duel Air bottle compartments, one (1) each side wheel well
- One (1) Hinged Tool Board, left side compartment
- Three (3) FlameFighter Walk-away Air Pack brackets, right side compartment
- Turtle Tile on floors, shelves and/or trays
- One (1) Suction Hose compartment for two (2) hoses with rear access, left side
- Ladder storage compartment under hosebed with rear access, right side
- Pike pole storage in ladder compartment
- One (1) Kussmaul 1200 battery charger with Viair Air compressor
- One (1) 120-volt Manual Shoreline connection
- Floor mounted console for electrical switches. Cab
- Code 3 Electronic Siren with 100-watt Federal speaker
- Two (2) Extenda-Lite HID 12-volt 150-watt telescopic lights, one (1) each side
- Weldon LED Warning Light Package
- Chevron pattern striping, rear 9' 1" Overall height
- 28' 3" Overall length
- 205" Wheelbase
- 139.45" Cab to Axle
- 12.000 FAWR
- 26,000 RAWR
- 38,000 GVWR









To view more photos of this unit, visit us on the web at www.AlexisFire.com.

We would like to thank the Osco Community Fire Protection District for their business.



Alexis Fire Equipment 109 East Broadway Alexis, Illinois 61412

