

TOP MOUNT PUMPER



PROTIVIN COMMUNITY FIRE DEPARTMENT PROTIVIN, IOWA

TECHNICAL SPECS

- Freightliner M2 106, 2-Door Chassis
- Cummins ISC, 330-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- On Spot Automatic Tire chains
- Heavy Duty 3/16" Aluminum Body
- ROM Roll Up Doors
- 1250-Gallon Poly Tank
- Waterous CXSC20C, 1250-GPM Pump
- Operator's panel located across top of apparatus
- Four (4) 2 1/2" Discharges, one (1) each side and two (2) rear
- Two (2) 2 1/2" Gated Suction, one (1) each side
- One (1) 3" Discharge over pump for Deck Gun
- Two (2) 1 1/2" Mattydale Preconnects behind the chassis cab
- Waterous Aquis 1.5 Foam system with 10-gallon foam tank
- Zico Hydraulic Folding tank rack for 2500-Gallon tank, left side
- Ladder/Pike pole storage right side behind compartments with rear access
- Suction hose storage for two (2) hose in the hosebed
- Two (2) Dual bottle Air bottle compartments, one (1) each side
- Three (3) walk-away air pack brackets, right side
- Progressive Dynamics on-board battery charger with Viair air compressor
- Kussmaul Super Auto Eject 120-volt shoreline
- Floor Mounted Console for Emergency switches with Map/binder storage, cab
- Code 3 Electronic Siren with 100-watt Federal speaker
- Three (3) Federal GHSCENE lights, one (1) each side and one (1) rear
- Two (2) Akron 12-volt telescopic lights, one (1) left side and one (1) rear
- Whelen LED Warning Light Package
- Chevron pattern striping, rear
- 10' 1" Overall height
- 31' 3" Overall length
- 242" Wheelbase
- 176.45" Cab to Axle
- 14,800 FAWR
- 30,000 RAWR
- 44,800 GVWR



To view more photos,
visit www.AlexisFire.com

WE WOULD LIKE TO THANK
THE PROTIVIN COMMUNITY FIRE
DEPARTMENT FOR THEIR BUSINESS.

