

TOP CONTROL PUMPER



To view more photos,
visit www.AlexisFire.com

WE WOULD LIKE TO THANK
THE SIGOURNEY COMMUNITY FIRE
DEPARTMENT INC FOR THEIR
BUSINESS.



SIGOURNEY COMMUNITY FIRE DEPARTMENT INC SIGOURNEY, IOWA

TECHNICAL SPECS

- Spartan Metro Star X MFD 10" raised roof Chassis
- Cummins ISC8.3, 380-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- Six (6) man cab seating with five (5) SCBA seats
- Heavy Duty 3/16" Aluminum Body
- ROM Roll Up Doors
- 24" Front bumper extension with 1 1/2" Preconnect and center hosewell
- 1000-Gallon Poly Tank
- One (1) 2 1/2" Fireman's Friend tank fill, rear
- Waterous CX, 1500-GPM Pump
- Pump operator's panel across top of apparatus
- Five (5) 2 1/2" Discharges, two (2) each side and one (1) rear
- One (1) 2 1/2" Gated Suction, left side
- One (1) 3" Discharge for deck gun over pump
- Two (2) 1 1/2" Cartridge Lay Preconnects, front of body
- Two (2) Triple bottle Air bottle compartments, right side wheel well
- One (1) Wheel chock compartment, left side wheel well
- Ladder/Pike pole storage compartment, right side with rear access
- Suction hose storage, right side of hosebed
- Kussmaul 1200 pump plus battery conditioner/air compressor
- Whelen Electronic Siren with 100-watt Cast Products speaker
- Whelen 12-volt LED scene light package, two (2) each side and one (1) rear
- Two (2) Extenda-Lite 12-volt 220-watt LED telescopic lights, one (1) each side
- Whelen LED Warning Light Package
- Diamond Grade Chevron pattern striping, rear
- 10' 4" Overall height
- 33' 7" Overall length
- 210" Wheelbase
- 156" Cab to Axle
- 20,000 FAWR
- 27,000 RAWR
- 47,000 GVWR

