SIDE CONTROL PUMPER





ST. ELMO FIRE PROTECTION DISTRICT

ST. ELMO, ILLINOIS

TECHNICAL SPECS

- International 4400 2-Door Chassis
- MaxxForce 9, 330-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- Heavy Duty 3/16" Aluminum Body
- · Box type flush style doors
- 1500-Gallon Poly Tank
- One (1) 2 1/2" Fireman's Friend tank fill, rear
- One (1) Newton 10" square manual dump with 36" extension, rear
- Hale Q flow, 1250-GPM Pump
- Left side control pump operator's panel
- Five (5) 2 ½" Discharges, two (2) each side and one (1) rear
- One (1) 3" Discharge over pump for deck gun
- Two (2) 1 ½" Mattydale Preconnects, across top of body
- Two (2) 2 ½" Gated Suctions, one (1) each
- Two (2) free floating hose wells in the running boards, one (1) each side
- Four (4) Single bottle Air bottle compartments, two (2) each side
- Six (6) Walk-away Air pack brackets, left side compartments
- Ladder and pike pole storage compartment with rear access, right side
- Hinged Folding Tank bracket for 2100gallon tank, right side compartment top

- Two (2) Suction hose storage gutters, left side compartment top
- · Manual battery recharge connection
- Quick couple Air connection for external compressor
- Chassis dash mounted console for emergency switches
- Two (2) Air Horns, one (1) each side of hood
- Whelen electronic Siren with 100-watt Cast products speaker
- Two (2) Unity deck lights, rear
- Two (2) Extenda-Lite 12-volt LED 220-watt telescopic lights, one (1) each side
- Whelen LED Warning Light Package
- · Chevron pattern striping, rear
- 9' 10" Overall height
- 27" 4" Overall length
- 201" Wheelbase
- 133.9" Cab to Axle
- 14,000 FAWR
- 30,000 RAWR
- 44,000 GVWR





To view more photos, visit www.AlexisFire.com

WE WOULD LIKE TO THANK THE ST. ELMO FIRE PROTECTION DISTRICT FOR THEIR BUSINESS.



