


- Cummins X15, 505-HP Diesel Engine
- Allison 4500 EVS Automatic Transmission
- Heavy Duty Stainless steel Body with Stainless steel Sub-Frame
- Hemmed Pan Style Compartment Doors
- 18" Front Bumper Extension with 2 1/2" Preconnect
- 3000-Gallon Wet Side Poly Tank
- One (1) 4" and one (1) 2 1/2" Tank Fill, rear
- Three (3) Newton 10" square Electric dumps with 18" Electric Extensions Hale DSD, 1250-GPM Pump with left side intermediate pump operator's panel
- Four (4) 2 1/2" Discharges, two (2) each side
- One (1) 2 1/2" Gated Suction, left side
- Two (2) 2" and one (1) 3" Deadlay hose beds, across top of body
- Two (2) SCBA pack compartments, one (1) each side between tandem wheels
- Two (2) Combination Fire Extinguisher/Air bottle compartments, wheel wells
- Custom Rear Bumper Extension compartments
- Two (2) Running board free floating hose wells, one (1) each side pump
- Two (2) Ziamatic Hydraulic folding tank brackets for 2500-gallon tanks
- Two (2) Suction hose storage gutters, one (1) each side
- Two (2) Pike pole storage tubes, one (1) each side compartment top
- Progressive Dynamics on-board battery charger
- Kussmaul Super Auto Eject 120-volt shoreline connection
- Audiovox Back-Up Camera System with 7" Color monitor and side view
- Floor mounted console for emergency switches, cab
- PowerCall Electronic Siren with two (2) PowerCall 100-watt speakers
- Federal Q2B Pedestal mounted Siren, front bumper
- Diamond Grade Chevron pattern striping, rear
- 10' 2" Overall height 20,000 FAWR
- 46,000 RAWR 35' 3" Overall length
- 176.4" Cab to Axle



 66.000 GVWR 266" Wheelbase













To view more photos and download spec sheet, please visit us at AlexisFire.com.

