











- · Cummins L9, 450-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- · Heavy Duty Stainless Steel Body and Sub-frame
- · ROM Roll Up Doors

TECHNICAL SPECIFICATIONS

- 3000-Gallon Wet side Poly Tank
- One (1) 2 1/2" Fire Programs Tank fill, rear
- One (1) Newton 10" square manual swivel dump with 36" extension
- Darley PSM 1500-GPM PTO Pump
- · Left side intermediate pump operator's panel
- Three (3) 2 1/2" Discharges, two (2) left side and one (1) right side
- One (1) 3" Discharge with 5" Storz, right side
- One (1) 1 ½" and one (1) 2 ½" Mattydale Preconnects, behind cab
- One (1) 2 1/2" Gated Suction, left side
- Folding Tank storage, right side compartment top
- · Suction hose storage, left side compartment top
- Manual battery recharge shoreline connection
- · Air coupling for external air compressor
- Floor mounted console for emergency switches, cab
- · Whelen Electronic Siren with 100-watt Whelen speaker
- Whelen LED Scene Light Package, one (1) light each side and two (2) rear
- Whelen LED Warning Light Package
- · Diamond Grade Chevron pattern striping, rear
- 10' 3" Overall height
- · 31' 6" Overall length
- · 238" Wheelbase
- 170.9" Cab to Axle
- 16,000 FAWR
- 40,000 RAWR
- 56,000 GVWR













To view more photos and download spec sheet, please visit us at AlexisFire.com.

