
VILLAGE OF NEW WASHINGTON / NEW WASHINGTON, OHIO















- Cummins L9 350-HP Diesel Engine
- Allison 3000 EVS Transmission
- Heavy Duty Stainless-Steel Body and Sub-Frame
- Five (5) Person Cab Seating w/ Four (4) SCBA Seats
- ROM Roll-up Doors
- Hale QMax150 XS 1500-GPM Pump
- 1000-Gallon Poly Tank
- 20-Gallon Foam Tank w/ FoamPro Single Tank Foam System
- Two (2) Running Board Hose Wells, one (1) Each Side
- Two (2) 6" Suctions w/ Akron Butterfly Valves, one (1) Each Side
- Five (5) 2 1/2" Discharges, two (2) Left, one (1) Right, two (2) Rear
- Two (2) 3" Discharge, one (1) Right Side, one (1) Deck Gun
- One (1) 2 ½" Gated Suction, Left Side Two (2) 1 ½" Cartridge Lay Preconnects One (1) 2 ½" Tank Fill, Rear
- Four (4) Dual Air Bottle Wheel Well Storage Compartments
- Progressive Dynamics On-board Battery Charger
- Kussmaul Super Auto Eject
- Floor Mounted Console for Emergency Switches w/ Binder Storage, Cab
- Whelen LED Warning Light and Scene Light Package
- Fire Research Spectra LED Telescopic Scene Lights
- Whelen Electronic Siren w/ 100-Watt Speaker
- Federal Q2B Siren
- Audiovox Back-up Camera System w/ 7" Monitor
- Ladder/Pike Pole/Suction Hose Storage, Through the Tank
- Diamond Grade Chevron Striping
- 9' 7" Overall Height
- 34' 3" Overall Length
- 272" Wheelbase
- 161" Cab to Axle
- 14,000 FAWR 30,000 RAWR
- 44,000 GVWR















To view more photos and download spec sheet, please visit us at AlexisFire.com.

