

CUSTOM SIDE CONTROL PUMPER #2521









TECHNICAL SPECIFICATIONS

- Spartan FC-94 MFD 10" Raised Roof Chassis
- 450 HP Cummins L9 Diesel Engine
- · Allison 3000 EVS Automatic Transmission
- EMS Compartment Center Rear Wall of Cab with ROM Door and 120V Power Strip
- · 24" Extended Front Bumper with Center Hose Well
- Front Bumper 1½" Preconnect
- 5" Front Suction adapted to 6" NST with Low Level Strainer Preconnect
- Two (2) 1½" Mattydale Preconnects
- 1200-Gallon Poly Tank
- · Heavy Duty Stainless-Steel Subframe & Body
- Stainless Steel Side Control Pump Module
- Hale QMAX 2000 gpm Split-Shaft Pump
- One (1) 2½" Gated Intake Left Side
- Two (2) 6" Intakes, One (1) Each Side
- Two (2) 2½" Discharges Left Side
- Two (2) 2½" Discharges Right Side
- One (1) 4" Discharge Adapted to 5" Storz with Handwheel Control Right Side
- One (1) 2 ½" Discharge Rear
- · Foam Pro 1600 Class A with 30 Gallon Tank
- ROM Painted Roll-Up Doors
- Three (3) Dual Bottle Wheel Well Compartments, One (1) Ahead Left Side, Two (2) Right Side

- One (1) 500# Roll Out Tray Each, L1/L3/R1/R3/ Rear Compartments
- PacTrac Tool Mounting Board Upper Rear Wall of L1/L3/R1/R3 Compartments
- Hinged PacTrac Tool Board L2 Compartment
- Three (3) Walk-Away Air Pack Brackets R2 Compartment
- Zico Hydraulic Ladder Rack with One (1) Hard Suction Right Side
- One (1) Hard Suction Rear Access Storage Compartment
- One (1) Back-Up Camera with Cab Display
- · Whelen Warning and Scene Light Package
- Two (2) Air Horns Recess Bumper Mounted
- · Whelen Electric Siren with 100W Speaker
- Kussmaul Battery Conditioner and Air Compressor with a Kussmaul 20-Amp 120V Super Auto-Eject Shoreline Inlet Left Side
- 10' 1" Overall Height
- · 33' 3" Overall Length
- · 199" Wheelbase
- 145" Cab to Axle
- 21,500 FAWR
- 31,000 RAWR
- 52,500 GVWR







