CUSTOM ENCLOSED TOP CONTROL PUMPER

COON CREEK FIRE & RESCUE / COON VALLEY, WISCONSIN


















- Cummins 450 HP L9 Diesel Engine
- Allison EVS 3000 Transmission
- Occupant Advanced Protection System
- 24" Front Bumper Extension with Preconnected Front Suction
- Cam In View 360 Bird's Eye View System
- Waterous CXVC 20 Single Stage 1500 GPM Pump
- Stainless Steel Enclosed Top Mount Pump Module
- FRC Pump Boss Pressure Governor
- Whelen LED Tank Level Gauges, Operator's Panel and Three (3) Sides
- Stainless Steel Manifold and Plumbing
- 2.5" Discharges- One (1) Left Side, One (1) Right Side & Two (2) Rear and 3" Discharges-One (1) Right Side & One (1) Left side
- Three (3) Cartridge Lay Preconnects, Two (2) 1.5" & One (1) 2.5"
- 2.5" Gated Intakes, One (1) Each Side
- One (1) Front Suction Intake and One (1) Rear Suction Intake
- Waterous Aquis 3.0 Single Tank Foam System with 20 Gallon Integral Tank
- Fixed Monitor Piping with an Akron Model 3430 Deck Gun
- Heavy Duty #304 Stainless Steel Body
- Sub-Frame-Heavy Duty Stainless Steel
- Three (3) Triple Wheel Well Air Bottle Compartments
- Customize Tool Storage, Adjustable Shelves, Vertical Pull-Out Boards, Hinged Swing Out Tool Boards
- Three (3) 6000 PSI Cascade System with Spacesaver Two Cylinder Fill Enclosure
- 1000 Gallon Poly Tank

TECHNICAL SPECIFICATIONS

- Whelen LED Warning Package including LED Arrow Stick
- Rub Rail LED Warning Lights and LED Ground Lights
- Whelen Electric Siren and Speaker & Federal Q Siren
- Whelen LED 12 V Scene Light Package & Akron 12 V LED Lift Lights
- Ladders Vertical Rear Storage and Two (2) Suction Hose Storage
- Fold Da Tank Storage in Hose Bed
- 11' Overall height
- 21,500 LB FAWR
- 33' 7" Overall length
- 149" Cab to Axle
- 27,000 LB RAWR
- 203" Wheelbase • 48,500 LB GVWR













To view more photos and download spec sheet, please visit us at AlexisFire.com.

