

3000 GALLON TANKER #2663



TECHNICAL SPECIFICATIONS

- Freightliner M2 106 2-Door Chassis
- Cummins 360 HP L9 Engine
- Allison 3000 EVS Automatic Transmission
- Heavy Duty Stainless Steel Body and Stainless Steel Subframe
- Stainless Steel Intermediate Pump Module
- Waterous CXVC 1500 GPM Pump
- Trident Air Prime System
- FRC Pump Boss Max Pressure Governor
- FRC Tankvision Water Tank Level Gauge
- Two (2) 6" Intakes, One (1) Each Side
- One (1) 2½" Gated Intake, Left Side
- Two (2) 2½" Discharges, Left Side and One (1) 2½" Discharge, Right Side
- One (1) 3" Discharge Adapted to 5" Storz, Right Side
- FoamPro 1600 Foam System with 30 Gallon Foam Tank
- One (1) 3" Discharge Dunnage Area with Akron Model 3433 Hi-Riser Deck Gun
- Two (2) 1½" Crosslay Preconnects with Deadlay
- Four (4) Dual Bottle Wheel Well Compartments
- ROM Roll Up Doors
- Fol-Da-Tank Storage for 3000 Gallon Fol-Da-Tank, Right Side Compartment Top
- Suction Hose Storage, Left Side Compartment Top
- Ladder Storage Brackets, Left Side
- 3000 Gallon Poly Wetside Tank with Wetside Hose Bed & Front Fill Tower
- One (1) 2½" FirePrograms Tank Fill, Rear Left Side
- One (1) 10" Newton Stainless Steel Swivel Dump with 36" Manual Extension, Rear
- 12 Volt Electrical System
- Progressive Dynamics Battery Charger with Viair Compressor, L1 Compartment
- Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Left Front Body Post
- Tecniq/Whelen LED Warning Light Package
- Whelen 200W Siren and 100W Speaker
- Four (4) Whelen 9S LED Scene Lights, One (1) Each Side and Two (2) Rear
- One (1) 24' 2-Section Ladder, One (1) 14' Roof Ladder with Hooks, One (1) 10' Attic Ladder, Two (2) 10' Lengths of 6" Hard Suction Hose and One (1) 3000 Gallon Fol-Da-Tank
- 10'-5" Overall Height
- 32'-2" Overall Length
- 236" Wheelbase
- 170.45" Cab to Axle
- 16,000 FAWR
- 44,000 RAWR
- 60,000 GVWR



