

3000 GALLON TANKER #2618



TECHNICAL SPECIFICATIONS

- Freightliner M2 112 2-Door Chassis
- Cummins 450 HP L9 Engine
- Allison 3000 EVS Automatic Transmission
- Heavy Duty Stainless Steel Body with Stainless Steel Subframe
- Pump Panel in L1 Compartment
- Waterous CLVK 500 GPM PTO Pump
- Trident Air Prime System
- FRC Pump Boss Pressure Governor
- FRC Tankvision Water Tank Level Gauge with Three (3) Whelen PSTANKS Strip Lites
- One (1) 4" Intake, Left Side in L1
- One (1) 2½" Discharge, Left Side in L1 and One (1) 2½" Discharge, Rear Left Side
- ROM Roll Up Doors
- Zico Electric Fol-Da-Tank Bracket for 3000 Gallon Fol-Da-Tank, Right Side Compartment Top
- Suction Hose Storage, Right Side on Fol-Da-Tank Rack
- Hose Tray Left Side Compartment Top for 150' of 1¾" Hose and 100' of 2½" Hose
- Hose Tray for Donut Roll, Rear Tail Step
- 3000 Gallon Poly Wetside Tank
- One (1) 2½" FirePrograms Tank Fill, Rear Left Side
- One (1) 4" FirePrograms Tank Fill with 4" Storz Elbow, Rear Right Side
- Three (3) 10" Newton Stainless Steel Dumps with 18" Electric Extensions, One (1) Each Side between the Rear Wheels and One (1) Rear
- 12 Volt Electrical System with NFPA Compliant Warning Lights
- Progressive Dynamics Battery Charger, L1 Compartment
- Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Left Front Body Post
- Kussmaul Auto Air Eject, Left Front Body Post
- Whelen LED Warning Light Package with Rear Arrow Stick
- Whelen 200W Siren and 100W Speaker
- Federal Q2B Siren
- Six (6) Whelen 9S LED Scene Lights, Two (2) Each Side and Two (2) Rear
- One (1) 12" Dual Row Rough Country Scene Light Bar, Front Bumper
- Two (2) 10' Lengths of 4½" Hard Suction Hose, One (1) 4½" Chrome Barrel Strainer, One (1) 4½" Low Level Strainer, and One (1) 3000 Gallon Fol-Da-Tank
- 10'-4" Overall Height
- 29'-5" Overall Length
- 197" Wheelbase
- 131.45" Cab to Axle
- 18,000 FAWR
- 46,000 RAWR
- 64,000 GVWR



