DAKOTA FIRE PROTECTION DISTRICT / DAKOTA, ILLINOIS
















- Cummins L9, 350-HP Diesel Engine Allison 3000 EVS Automatic Transmission
- Heavy Duty Stainless Steel Body and sub-frame
- ROM Roll Up Doors
- 3000-Gallon Poly Tank
- One (1) 4" Fireman's Friend Tank fill, rear
- One (1) Newton 10" square manual swivel dump with 36" extension
- Darley PSM 1250-GPM PTO Pump
- Left side intermediate pump operator's panel
- Three (3) 2 1/2" Discharges, two (2) left side and one (1) right side
- One (1) 3" Discharge, right side
 One (1) 1 %" and one (1) 2 ½" Mattydale Preconnects, behind cab
 One (1) 2 ½" Gated Suction, left side
- Two (2) Dual bottle Air bottle compartments, one (1) each side wheel well
- Three (3) Walk-away air pack brackets, left side compartment
- Roll out drop down folding tank storage, left side compartment op Suction hose storage, right side compartment top under tank "T"
- Ladder brackets, right side
- One (1) Hose storage box, rear tailstep area
- Manual battery recharge shoreline connection
- Air coupling for external air compressor
- One (1) Audiovox Back-up Camera system with 7" color monitor
- Code-3 Electronic Siren with 100-watt Code-3 speaker Code-3 LED Scene Light Package
- Code-3 LED Warning Light Package
- Diamond Grade Chevron pattern striping, rear
- 10' 2" Overall height
- 31' 6" Overall length
- 236" Wheelbase
- 170.45" Cab to Axle
- 16,000 FAWR
- 40,000 RAWR
- 56,000 GVWR













To view more photos and download spec sheet, please visit us at AlexisFire.com.

