

## TOP MOUNT PUMPER #2599



### TECHNICAL SPECIFICATIONS

- International HV607 2-Door Chassis
- Cummins L9 450 HP Diesel Engine
- Allison 3000 EVS Transmission
- Heavy Duty Stainless Steel Body with Stainless Steel Subframe
- Stainless Steel Top Mount Pump Module with Stainless Steel Subframe
- Two (2) Stainless Steel Free Floating Hose Wells, One (1) in Each Side Running Board
- Waterous CXVC20 1500 GPM Pump
- Trident 3-Location Automatic Air Primer
- FRC Pump Boss Pressure Governor Monitoring System
- FRC TankVision Water Tank Level Gauge
- Two (2) 6" Intakes with Electric MIV Valves, One (1) Each Side
- One (1) 5" Intake Adapted to 6" NSTM, Rear Right Side
- One (1) 2½" Gated Intake, Left Side
- Four (4) 2½" Discharges, Two (2) Each Side
- Two (2) 2½" Discharges, Rear One (1) Each Side
- One (1) 3" Discharge, Right Side
- One (1) 3" Discharge Dunnage Area with TFT Crossfire Deck Gun and Extenda-Gun
- FoamPro 1600 Foam System with 20 Gallon Foam Tank
- Two (2) 1½" Crosslay Preconnects at Front of Walkway
- One (1) 2½" Bumper Extension Preconnect
- ROM Roll-Up Doors
- Two (2) Triple Wheel Well Air Bottle Compartments
- Two (2) Fire Extinguisher Wheel Well Compartments
- Ladder Storage Compartment, Horizontal Through the Tank in the Rear Compartment
- Suction Hose Storage for Three (3) Sections of Hard Suction Hose, One (1) Left Squirrel Tail and Two (2) Right
- AFE Stainless Steel Rear Access Ladder with Flip Down Step, Left Side
- 1250 Gallon Poly Tank
- 12 Volt Electrical System
- Tecniq/Whelen LED Warning Light Package with Rear Arrow Stick
- Manual Battery Recharge Receptacle for In Station Charger
- Whelen 200W Siren and 100W Speaker
- Four (4) FRC Spectra LED Scene Lights, One (1) Each Side and Two (2) Rear
- Four (4) FRC Spectra LED Telescopic Lights, One (1) Each Side of the Pump Module and One (1) Each Side at the Rear of the Body
- One (1) 10' Attic Ladder, One (1) 14' Roof Ladder with Hooks, One (1) 24' 2-Section Ladder, One (1) 35' 3-Section Ladder, and Four (4) 10' Lengths of 6" Suction Hose
- 10' Overall Height
- 34'-4" Overall Length
- 250" Wheelbase
- 182.9" Cab to Axle
- 16,000 FAWR
- 30,000 RAWR
- 46,000 GVWR



