

## REAR MOUNT 1500 GPM PUMPER #2527



### TECHNICAL SPECIFICATIONS

- International HV607 Crew Cab Chassis
- Cummins L9 360 HP Diesel Engine
- Allison 3000 EVS Transmission
- Heavy Duty Stainless Steel Body with Stainless Steel Subframe
- Rear Mount Pumping System
- Waterous CXVK 1500 GPM Rear Mount Pump
- Trident Air Primer
- Diesel Fired Pump Heater
- Rear Mount Pump Operator's Panel Behind Roll Up Door
- FRC Pump Boss Pressure Governor Monitoring System
- FRC Tankvision Water Tank Level Gauge
- One (1) 6" Intake, Rear
- One (1) 2½" Gated Intake, Rear
- Two (2) 2½" Discharges, Rear
- One (1) 3" Discharge Adapted to 2½" MNST, Rear
- One (1) 3" Deck Gun Discharge Rear Over Pump in Hose Bed Center
- FoamPro 1600 Foam System with 20 Gallon Foam Tank
- One (1) 1½" and One (1) 2½" Crosslay Preconnects – Front Bumper
- ROM Roll-Up Doors
- Two (2) Dual Wheel Well Air Bottle Compartments, One (1) Each Side
- Two (2) Triple Wheel Well Air Bottle Compartments, One (1) Each Side
- Zico Overhead Hydraulic Ladder Rack, Dual Arm
- Suction Hose Storage for Two (2) lengths Hose, Left Side Upper
- 1000 Gallon Poly Tank
- 12 Volt Electrical System with NFPA Compliant Warning Light Package
- Whelen LED Warning Light Package
- Progressive Dynamics Battery Charger with Viar Compressor
- Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Left Side
- Kussmaul Auto Air Eject
- Whelen 200W Siren and 100W Speaker
- Two (2) FireTech HiViz 40" LED Scene Light Bars, One (1) Each Side
- One (1) FireTech HiViz 21" LED Scene Light Bars, Rear Center
- One (1) FireTech HiViz 21" LED Brow Light
- One (1) 10' Attic Ladder, One (1) 14' Roof Ladder with Hooks, One (1) 24' 2-Section Ladder, and Two (2) 10' Lengths of 6" Suction Hose
- 10' Overall Height
- 31' 8" Overall Length
- 201" Wheelbase
- 89.9" Cab to Axle
- 16,000 FAWR
- 30,000 RAWR
- 46,000 GVWR





