

2000 GALLON TANKER #2695



TECHNICAL SPECIFICATIONS

- Freightliner M2-106 4X4 2-Door Chassis
- Cummins 360 HP L9 Engine
- Allison 3000 EVS Automatic Transmission
- Heavy Duty Aluminum Body and Subframe
- Intermediate Pump Module
- Waterous CXD-TPA 1250 GPM PTO Pump
- Trident Air Prime System
- FRC Pump Boss Pressure Governor
- FRC Tankvision Water Tank Level Gauge
- Two (2) 6" Intakes, One (1) Each Side
- One (1) 2½" Gated Intake, Left Side
- Two (2) 2½" Discharges, Left Side and One (1) 2½" Discharge, Right Side
- One (1) 3" Discharge Adapted to 5" Storz, Right Side
- One (1) 1½" and One (1) 2½" Crosslay Preconnects with Deadlay Hose Bed
- One (1) Elkhart Brush Hawk Bumper Turret
- One (1) 1½" Bumper Extension Preconnect
- One (1) Booster Reel with 100' of 1" Booster Hose, Rear Panel Below Dump
- ROM Roll Up Doors
- Fol-Da-Tank Storage for 2100 Gallon Fol-Da-Tank, Left Side Compartment Top
- Suction Hose Storage, Right Side Compartment Top
- Custom Ladder Brackets, Right Side Compartment Top
- 2000 Gallon Poly Wetside Tank with Wetside Hose Bed & Front Fill Tower
- One (1) 2½" FirePrograms Tank Fill, Rear Left Side
- One (1) 10" Newton Stainless Steel Swivel Dump with 36" Manual Extension, Rear
- 12 Volt Electrical System
- Iota DLS-45-IQ4 Battery Charger, L1 Compartment
- Manual 120V Shoreline Connection, Left Front Rear Wheel Well
- Kussmaul Auto Air Eject
- Whelen LED Warning Light Package
- Whelen 200W Siren and 100W Speaker
- Six (6) Whelen 9S LED Scene Lights, Two (2) Each Side and Two (2) Rear
- One (1) FireTech HiViz 46" LED Brow Light
- Two (2) 10' Lengths of 6" Hard Suction Hose and One (1) 2100 Gallon Fol-Da-Tank
- 10'-1" Overall Height
- 28'-1" Overall Length
- 201" Wheelbase
- 135.45" Cab to Axle
- 16,000 FAWR
- 31,000 RAWR
- 47,000 GVWR



