

1500 GPM TOP CONTROL PUMPER #2511



TECHNICAL SPECIFICATIONS

- Spartan FC-94 MFD 10" Raised Roof
- Cummins L9 450 HP Diesel Engine
- Allison 3000 EVS Transmission
- Heavy Duty Stainless-Steel Body and Subframe
- Four (4) Person Cab
- ROM Painted Roll-Up Doors
- Hale DSD 1500 gpm Pump
- Trident Air Primer, Two (2) Location
- 750 Gallon Poly Tank
- Stainless-Steel Top Mount Pump Module w/ 22" Midship Walkway
- Two (2) 6" Intakes, One Each Side, Left and Right
- One (1) 5" Front Intake
- One (1) 2½" Gated Intake, Left Side
- Three (3) 2½" Discharges, Two (2) Left and One (1) Right Side
- One (1) 3" Discharge Reduced to 2½" MNST, Rear
- One (1) 3" Discharge Adapted to 5" Storz, Right Side
- Two (2) 1½" Mattydale Preconnects Deep Cut
- TFT Crossfire XFC-42 Deck Gun with 18" Extend-A-Gun
- Two (2) Free Floating Hose Wells, One Each Left and Right Side
- Running Boards
- Two (2) Triple Air Bottle Wheel Well Compartments, One (1) Each Side Ahead
- One (1) Fire Extinguisher Wheel Well Compartment, Right Side Behind
- Hinged PacTrac Tool Board, L2 Compartment
- One (1) 500# Roll Out Tray, L3 Compartment
- One (1) 500# Roll Out Tray, Rear Compartment
- AFE Stainless Steel Top Access Ladder
- Kussmaul Battery Conditioner and Air Compressor with a Kussmaul 20-Amp 120V Super Auto-Eject Shoreline
- Whelen LED Warning Light Package
- FireTech Scene Light Package
- 9' 10" Overall Height
- 36' 1" Overall Length
- 224" Wheelbase
- 170" Cab to Axle
- 21,500 FAWR
- 31,500 RAWR
- 53,000 GVWR



