











Five (5) Person Cab

Stainless-Steel Top Mount Pump Module with 22" Midship Walkway Hale DSD150 Single Stage Split-Shaft 1500 GPM Pump

Trident Air Prime System

FRC Pump Boss Pressure Governor & Monitoring System

Two (2) 6" Intakes, One (1) Each Side

One (1) 21/2" Gated Intake, Left Side

One (1) 2½" Tank Fill Adapted to 3" FirePrograms Valve Two (2) 2½" Discharges, Left Side One (1) 2½" Discharge, Right Side

One (1) 3" Discharge, Right Side Adapted to 5" Storz

One (1) 3" Discharge, Rear Adapted to 21/2" NST

Two (2) 11/2" Mattydale Preconnects

One (1) Booster Reel 150' of 1", Rear

1000-Gallon Poly Tank

TECHNICAL SPECIFICATIONS

AFE Stainless-Steel Top Access Ladder

Hose Bed with One (1) Divider, Three (3) LED Lights, Hypalon Cover Ladder Storage Capacity: One (1) 24' 2 Section Ladder, One (1) 14' Roof

Ladder, One (1) 10' Attic Ladder, Rear Through Tank

Two (2) 10' x 6" Hard Suction Hoses, Rear Through Tank Three (3) Dual Wheel Well Air Bottle Compartments, One (1) Left, Two Right

One (1) Center Console with Switches

Progressive Dynamics Battery Charger with Viair Compressor Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Under Cartridge Lay

Whelen LED Warning Light Package

Whelen Scene Lights, One (1) Each Side, Two (2) Rear

Whelen Electric Siren & 100W Speaker

9'11" Overall height

34' Overall length

258" Wheelbase

145.2" Cab to Axle

16.00 FAWR

30,000 RAWR 46.000 GVWR

















To view more photos and download spec sheet, please visit us at AlexisFire.com.

