

## SIDE CONTROL PUMPER #2588



### TECHNICAL SPECIFICATIONS

- Spartan Metro Star MFD Chassis with 10" Raised Roof
- Cummins k9 450 HP Diesel Engine
- Allison 3000 EVS Transmission
- Heavy Duty Stainless Steel Body with Stainless Steel Subframe
- Stainless Steel Side Control Pump Module with Stainless Steel Subframe
- Hale QMAX-XS 1500 GPM Pump
- Trident Air Primer
- FRC Pump Boss Pressure Governor Monitoring System
- FRC TankVision Water Tank Level
- Two (2) 6" Intakes, One (1) Each Side
- One (1) 5" Front Intake with 6" Swivel Elbow, Right Side Bumper Extension
- One (1) 2½" Gated Intake, Left Side
- One (1) 2½" Discharge, Left Side and One (1) 2½" Discharge, Right Side
- Two (2) 2½" Discharges, Rear One (1) Each Side
- One (1) 3" Discharge with 5" Storz Elbow, Right Side
- One (1) 3" Discharge Dunnage Area with TFT Extenda-Gun
- Two (2) 1½" Crosslay Preconnects
- One (1) 1½" Bumper Extension Preconnect
- Three (3) Dual Air Bottle Wheel Well Compartments
- ROM Painted Roll Up Doors
- Ladders Storage Compartment Vertical in Hose Bed, Right Side
- Suction Hose Storage in Hose Bed Above the Ladder Storage
- 1000 Gallon Poly Tank
- 12 Volt Electrical System with NFPA Compliant Warning Light Package
- Kussmaul Chief 4012 Battery Charger with 120 Volt Kussmaul Pump
- Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Left Side of Cab
- Whelen LED Warning Light Package with Rear Arrow Stick
- Whelen 200W Siren and 100W Speaker
- Federal Q2B Siren
- Two (2) FireTech HiViz 40" LED Scene Bars, One (1) Each Side
- Two (2) Whelen 9S LED Scene Lights, One (1) Each Side Rear
- One (1) FireTech HiViz 72" LED Brow Light
- Two (2) Whelen 9S LED Scene Lights, One (1) Each Side of the Cab
- One (1) 10' Attic Ladder, One (1) 14' Double Ended Roof Ladder with Hooks, and One (1) 24' 2-Section Ladder
- 9'-11" Overall Height
- 30'-7" Overall Length
- 173" Wheelbase
- 119" Cab to Axle
- 21,500 FAWR
- 27,000 RAWR
- 48,500 GVWR



