

## 3000 GALLON TANKER #2647



### TECHNICAL SPECIFICATIONS

- International HX620 2-Door Chassis
- Cummins X15 500 HP Engine
- Allison 4500 EVS Automatic Transmission
- Heavy Duty Stainless Steel Body and Stainless Steel Subframe
- Stainless Steel Side Control Pump Module with Stainless Steel Subframe
- Two (2) Stainless Steel Free Floating Hose Wells, One (1) in Each Side Running Board
- Waterous CXVC 1500 GPM Pump
- Trident Air Prime System
- FRC Pump Boss Pressure Governor
- FRC Tankvision Water Tank Level Gauge with Three (3) MaxVision Strip Lites
- Two (2) 6" Intakes, One (1) Each Side
- One (1) 2½" Gated Intake, Left Side
- Two (2) 4" Discharges Adapted to 4" Storz, One (1) Each Side
- One (1) 2½" Discharge, Right Side
- Two (2) 1½" and One (1) 2½" LA Style Crosslay Preconnects
- ROM Painted Roll Up Doors
- Two (2) Fol-Da-Tank Bracket for 3000 Gallon Fol-Da-Tanks, One (1) Each Side Compartment Top
- Suction Hose Storage for Three (3) Lengths, Two (2) Left and One (1) Right
- 3000 Gallon Poly Elliptical Tank with Stainless Steel Wrap
- One (1) 4" FirePrograms Tank Fill, Rear Right Side Adapted to 4" Storz
- One (1) 10" Newton Stainless Steel Electric Dump with 18" Electric Extension, Rear
- Two (2) 8" Round Air Dumps with 8" Air Operated Extension, One (1) Each Side
- 12 Volt Electrical System with NFPA Compliant Warning Light Package
- Progressive Dynamics Battery Charger with Viar Compressor, L1 Compartment
- Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Below Driver's Door
- Whelen LED Warning Light Package with Emitter and Rear Arrow Stick
- Whelen 200W Siren and 100W Speaker
- Six (6) Whelen 9S LED Scene Lights, Two (2) Each Side and Two (2) Rear
- One (1) FireTech HiViz LED Brow Light
- Two (2) 3000 Gallon Fol-Da-Tanks
- 10'-8" Overall Height
- 33'-4" Overall Length
- 242" Wheelbase
- 172.9" Cab to Axle
- 20,000 FAWR
- 46,000 RAWR
- 66,000 GVWR



