

TANKER #2470









TECHNICAL SPECIFICATIONS

- · Heavy Duty Stainless Steel Body and Sub-Frame
- · ROM Series IV Satin Finish Roll-Up Doors
- Two (2) compartments Each side with Dual LED Strip Lights
- 3000 Gallon Fol-Da-Tank Storage, Above Right side compartments
- Storage for Two (2) 10' lengths of hard suction hose, Above Left compartments
- · Waterous CXV 1250 GPM PTO Pump
- Alexis Custom Stainless Steel Cast Manifold System with 10 Year Warranty
- · Trident Air Prime System
- · Stainless Steel Side Mount Pump Module
- Two (2) Hose Wells, One (1) Each side of Pump Module
- FRC Pump Boss Pressure Governor & Monitoring System
- Two (2) 6" Intakes, One (1) Each Side
- One (1) 21/2" Gated Intake, Left Side
- One (1) 2½" and One (1) 4" Adapted to 5" Storz Rear Tank Fills
- Two (2) 21/2" Discharges, Left Side
- · One (1) 21/2" Discharge, Right Side
- One (1) 3" Discharge, Right Side Adapted to 5" Storz
- One (1) 11/2" and One (1) 21/2" Mattydale Preconnects

- · One (1) Newton 10" Rear Manual Swivel Dump
- 3000-Gallon Poly Tank
- · Wetside Hosebed with Rear Fill Tower
- Two (2) Dual Air Bottle Compartments, One (1) Each side Ahead of Wheel Wells
- · One (1) Center Console with Switches
- Progressive Dynamics Battery Charger, L1 Compartment
- Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Left Front Body Post
- · Whelen Warning and Scene Light Package
- One (1) Rear Mounted Audiovox Backup Camera with Cab Display
- Four (4) Folding Steps, Rear
- International HV607 Conventional Chassis
- · Cummins L9 360 HP Engine
- · Allison 3000 EVS Automatic Transmission
- 9' 11" Overall Height
- · 32' 4' Overall Length
- · 238" Wheelbase
- 170.9" Cab to Axle
- 16,000 FAWR
- 40,000 RAWR
- 56,000 GVWR







