

## **1500 GPM MINI PUMPER #2476**



## **TECHNICAL SPECIFICATIONS**

- Ford F-550 4×4 Super Duty Crew Cab Chassis
- 6.7L 4V OHV V8 Turbo Diesel Engine
- · TorgShift 10-Speed Automatic Transmission
- · Heavy Duty Stainless Steel Body and Stainless Steel Subframe
- · Stainless Steel Pump Panel in L1/R1 with Stainless Steel Subframe
- · N-Fab Podium Black Cab Side Steps
- Go Industries Brush Guard with Hitch and Rear Hitch with Winch Wiring
- · Warn Zeon 10 Multi-Mount Winch
- Hale DSD 1500 GPM Split Shaft Pump with Hale ESP Priming Pump
- FRC PumpBoss Pressure Governor
- FRC TankVision Water Tank Level Gauge
- · Two (2) 6" Intakes, One (1) Each Side
- One (1) 5" Rear Intake, Adapted to 6" NSTM
- One (1) 21/2" Gated Intake Left Side
- Two (2) 2½" Discharges, Left Side, One (1) 2½" Discharge, Right Side
- One (1) 3" Discharge Adapted to 5" Storz, Right Side
- One (1) 2½" Discharge, Front of Hose Bed on the Right Side
- One (1) 3" Deck Gun Discharge
- Two (2) 11/2" Cartridge Lay Preconnect, L1/R1 Compartments
- · One (1) Booster Reel Rear Compartment with 100' of 1" Hose
- Three (3) Single Wheel Well Air Bottle Compartments
- · ROM Painted Roll-Up Doors
- 300 Gallon Poly Tank
- 12 Volt Electrical System with NFPA Compliant Warning Light Package
- Progressive Dynamics Charger with Viair Compressor and Auxiliary Air Tank
- Kussmaul 120V 20A Super Auto Eject, Left Side Rear Wheel Well
- Tecniq LED Warning and LED Scene Light Package
- Whelen Electronic Siren & 100W Speaker
- FireTech HiViz 21" LED Brow Light Mounted on the Brush Guard
- · Hard Suction Storage Left Side and Ladder Storage Right Side
- One (1) 10' Attic Ladder and One (1) 16' 2-Section Ladder
- · 8' Overall Height
- · 26'-10" Overall Length
- · 203.8" Wheelbase
- 84" Cab to Axle7,500 FAWR
- 14,700 RAWR
- 19,500 GVWR

















