LEROY FIRE PROTECTION DISTRICT / LEROY, ILLINOIS
















- Cummins L9 Diesel 450 HP Engine
- Allison EVS 3000 Transmission
- Occupant Advanced Protection System
- EMS Compartment in Crew Area
- 18" Extended Front Bumper with Full Width Hose Tray
- Heavy-Duty Stainless-Steel Body
- Sub-Frame- Stainless Steel
- Top Control Module with Pistol Grip Controls Darley PSM 1500 GPM Split shaft Pumping System
- Stainless Steel Manifold and Plumbing
- Trident 3-Barrel Air Primer, Two (2) Location
- FRC Pump Boss Pressure Governor System
- Discharges-2.5"-One (1) Left, Two (2) Right, & One (1) Rear. One (1) 4" Discharge-Left. Two (2) 1.5" Cartridge Lay Preconnects. One (1) Bumper Preconnect. One (1) Fixed Monitor Piping for Deck Gun
- Two (2) 2.5" Gated Intakes, One (1) Each Side
- Two (2) Electric MIV Intake Valves, One (1) Each Side.
- One (1) Rear Suction Intake
- Two (2) Triple Wheel Well Air Bottle Compartments
- Painted ROM Roll Up Doors
- Assortment of Adjustable Shelves, Roll Out Trays, Hinged Tool boards, Aluminum Peg Board on Compartment Walls
- Horizontal Ladder/Suction Hose Storage Through the Tank 1000 Gallon Poly Tank with Fire Program 2.5" Tank Fill
- Whelen Warning Light Package
- Rub Rail LED Warning Lights & LED Ground Lights
- Whelen Electric Siren & Speaker & Q Siren
- Whelen TAL 65 LED Arrow Stick
- Fire Tech 12 V Scene Light System
- Back Up Camera System
- 9' 10" Overall height
- 34' 10" Overall length
- 224" Wheelbase
- 164" Cab to Axle 20.000 LB FAWR
- 27,000 LB RAWR
- 47,000 LB GVWR















To view more photos and download spec sheet, please visit us at AlexisFire.com.

