

CUSTOM SIDE CONTROL PUMPER



CITY OF PEKIN FIRE DEPARTMENT
PEKIN, ILLINOIS

TECHNICAL SPECS

- Spartan Metro Star ELFD with 10" raised roof Chassis
- Cummins ISL9, 450-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- Four (4) man cab seating with three (3) SCBA seats
- Heavy Duty 3/16" Aluminum Body with ROM Roll up compartment doors
- 750-Gallon Poly Tank
- Waterous CSU 1250 GPM Pump with left side operator's panel
- Four (4) 2 1/2" Discharges, two (2) left, one (1) right side and one (1) rear
- One (1) 2 1/2" Mattydale Preconnect, across top of pump module
- Two (2) 3" Discharges, One (1) right side and one (1) over pump for Deck Gun
- Elkhart Stinger Deck Gun with TFT Extend-a-Gun
- One (1) 2 1/2" Gated Suction, left side
- 28" Front bumper extension with two (2) 1 1/2" Cartridge Lay preconnects
- One (1) Vertical Pull out tool board, left side
- Two (2) Hannay Dual Hydraulic Hose Reels, left side
- One (1) Booster Reel with 100' of 1" hose, rear compartment
- EMS Cabinet, chassis cab rear wall
- Three (3) Triple Bottle Air bottle compartments, one (1) left and two (2) right
- Zico hydraulic ladder rack with Pike Pole storage, right side
- Suction hose storage compartment for one (1) hose, upper left side
- Kussmaul 1200 on-board battery charger with Super Auto Eject shoreline
- Federal Q2B mechanical Siren, front bumper
- Whelen Electronic siren with one (1) Cast products 100-watt speaker
- Two (2) Air Horns, front bumper
- Two (2) Fire Research Spectra telescopic LED floodlights, one (1) each side
- One (1) FRC 12-volt LED Brow light
- One (1) Federal Visibeam wireless spotlight, cab roof center
- Four (4) Whelen LED Scene lights, One (1) each side and two (2) rear
- Whelen LED Warning Light Package
- Diamond Grade Chevron pattern striping, rear
- 9' 10" Overall height
- 33' 2" Overall length
- 202" Wheelbase
- 128" Cab to Axle
- 20,000 FAWR
- 27,000 RAWR
- 47,000 GVWR



To view more photos,
visit www.AlexisFire.com

**WE WOULD LIKE TO THANK
THE CITY OF PEKIN FIRE DEPARTMENT
FOR THEIR BUSINESS.**



