3000-GALLON EQUALIZER TANKER







TECHNICAL SPECS

- Freightliner 108 SD 2-Door Chassis
- · Cummins ISL, 400-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- Heavy Duty 3/16" Aluminum Body
- · ROM Roll Up Doors
- 3000-Gallon Poly Tank
- One (1) 2 ½" and one (1) 4" Fireman's Friend Tank fills, rear
- One (1) Newton 10" square manual swivel dump with 36" extension, rear
- · Darley PSM, 1250-GPM Pump
- Intermediate stainless steel pump operator's panel left side under tank
- Four (4) 2 ½" Discharges, two (2) left, one (1) right side and one (1) rear
- · One (1) 3" Discharge, right side
- One (1) 2 1/2" Gated Suction, left side
- Two (2) 1 ½" Mattydale Preconnects, above module between cab and tank
- One (1) 5" Front Suction, through the bumper
- Folding Tank storage, right side compartment top
- Suction Hose storage, left side compartment top
- Two (2) Dual bottle Air bottle compartments, one (1) each side wheel wells
- · Ladder storage brackets, right side
- Attic ladder and pike pole storage, left side compartment top

- Progressive Dynamics on-board battery charger with Viair Air compressor
- Kussmaul Super Auto Eject 120-volt shoreline connection
- Two (2) Air Horns, one (1) each side of hood
- Whelen Electronic Siren with Whelen 100-watt speaker
- Six (6) Federal GHSCENE lights, two (2) each side and two (2) rear
- Whelen LED Warning Light Package
- · Chevron pattern striping, rear
- · 10' 2" Overall height
- · 32' 3" Overall length
- · 239" Wheelbase
- 173.5" Cab to Axle
- 16,000 FAWR
- 40,000 RAWR
- 56,000 GVWR





To view more photos,

WE WOULD LIKE TO THANK
THE STEWARDSON FIRE & AMBULANCE
DISTRICT FOR THEIR BUSINESS.



