











0



- 450 HP Cummins L9
- Allison 3000 EVS Automatic Transmission
- Six (6) Person cab with five (5) SCBA seats
- 24" Front Bumper Extension with one (1) 1 1/2" Preconnect and Center
- Progressive Dynamics Battery Conditioner with VIAIR Auxiliary Compressor
- Heavy Duty Aluminum Subframe & Aluminum Body ROM Series IV Satin Finish Roll Up Doors

- 1000 Gallon Poly Water Tank Top Control Pump Module Hale QMAX-XS 150 1500 GPM Split Shaft Pump
- One (1) 5" Front Suction Two (2) 6" Suctions, one (1) each side
- One (1) 2 ½" Gated Suction, Left Side Four (4) 2 ½" Discharges, Two (2) Left, One (1) Right, & One (1) Rear
- One (1) 3" Discharge, Right Side
- One (1) 3" Fixed Monitor Piping Over Pump Compartment Two (2) 1 1/2" Cartridge Lay Preconnects
- Low Hose Bed with One (1) Divider
- Electronically Controlled Ladder Rack
- Suction Hoses, Pike Poles and Attic Ladder Storage Through the Tank Aluminum Rub Rails with LED Ground Lights and LED Warning Lights
- Duradeck Tile on floors of the compartments
- Fire Tech 12 Volt Scene Lights Package
- 9' 10" Overall Height
- 208" Wheelbase
- 20,000 FAWR
- 27,000 RAWR
- Whelen LED Warning Light Package Federal Q2B mechanical Siren, front bumper
 - Diamond Grade Chevron Striping, Rear
 - 34' Overall Length
- 154" Cab to Axle
- 47,000 GVWR











To view more photos and download spec sheet, please visit us at AlexisFire.com.

