NICHOLS VOLUNTEER FIRE DEPARTMENT / NICHOLS, IOWA
















- Cummins L9 350-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- Stainless steel Body and Sub Frame
- ROM Roll Up Doors 2000 Gallon Wet side Poly Tank
- One (1) 4" Fireman's Friend Tank fill, rear
- One (1) Newton 10" square manual swivel dump with 36" extension Waterous CXS, 1500-GPM Pump
- Left side intermediate pump operator's panel
- Three (3) 2 1/2" Discharges, two (2) left and one (1) right side
- One (1) 3" Discharge, right side
- One (1) 2 1/2" Gated Suction, left side
- Two (2) 1 1/2" Mattydale Preconnects, behind cab
- Folding tank storage for 2100-gallon tank, top of compartments right side
- Suction hose storage, top of compartments left side
- Progressive Dynamics on-board battery charger
- Blue Seas Auto Eject 120-volt shoreline connection
- Kussmaul Air Eject
- Floor mounted console for emergency switches, cab
- Whelen Electronic Siren with 100-watt Whelen speaker
- Whelen LED Scene Light Package
- Whelen LED Warning Light Package
- Diamond Grade Chevron pattern striping, rear
- 10' Overall height
- 25' 10" Overall length
- 200" Wheelbase
- 134.45" Cab to Axle
- 14,600 FAWR
- 30,000 RAWR
- 44,600 GVWR













To view more photos and download spec sheet, please visit us at AlexisFire.com.

