

3000-GALLON TANKER #2512



TECHNICAL SPECIFICATIONS

Heavy Duty 304 Stainless Steel Body and 304 Stainless-Steel Sub Frame with Lifetime Warranty

ROM Series IV Satin Finish Roll-Up Doors

Zico Hydraulic Fol-Da-Tank Bracket Left Side

Suction Hose Storage Right Side

Waterous CLVK 500 GPM PTO Pump

Alexis Custom Stainless Steel Cast Manifold system with 10 Year Warranty

Trident Air Prime System

Stainless-Steel Intermediate Pump Module

FRC Pump Boss Pressure Governor & Monitoring System

One (1) 4" Intake - Left Side

One (1) 21/2" Discharge, Left Side

One (1) 21/2" Discharge, Right Side

One (1) 11/2" and One (1) 21/2" Mattydale Preconnects

with Hypalon Cover

3000-Gallon Poly Tank

One (1) 10" Newton Stainless-Steel Manual Swivel Dump with Electric Valve

Two (2) Rear FirePrograms Tank Fills – one (1) $4" \times 5"$ Storz with elbow and one (1) $2\frac{1}{2}"$

Wetside Hosebed with Hypalon Cover

Progressive Dynamics Battery Charger with Viair Compressor, L1 Compartment

Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Left Rear Wheel Well

Whelen Warning and Scene Light Package

Whelen Siren and Speaker

Federal Q2B Recess Mounted

Freightliner M2 106 Conventional Chassis

Cummins 360 HP L9 Engine

Allison 3000 EVS Automatic Transmission 9' 9" Overall height 16,000 FAWR 30'-11" Overall length 40,000 RAWR 233" Wheelbase 56,000 GVWR

167.4" Cab to Axle

















