

COMMERCIAL TOP CONTROL PUMPER

ORLEANS FIRE DISTRICT / ORLEANS, NY



ALEXIS



THANK YOU TO THE ORLEANS FIRE DISTRICT FOR THE PURCHASE OF THIS UNIT.



- TECHNICAL SPECIFICATIONS**
- Freightliner M2 Crew Cab
 - Cummins L9 360 HP Diesel Engine
 - Allison EVS 3000 Transmission
 - Heavy-Duty Stainless-Steel Body
 - Sub-Frame -Stainless Steel
 - Top Control Pump Module
 - Hale QMAX-XS 1250 GPM Pump
 - Trident 3-Barrel Air Primer, Two (2) Location
 - FRC Pump Boss Pressure Governor & FRC Water Tank Gauge
 - Pump Heat Enclosure-Hot Water Heat
 - Stainless Steel Manifold and Plumbing
 - Discharges-2.5"-Two (2) Left Side, Two (2) Right Side, One (1) Rear.
 - Preconnects-Two (2) 1.5" Cartridge Lay
 - Fixed Monitor Piping for Deck Gun
 - One (1) 2.5" Gated Intake
 - Rear Suction Intake-Electric Controlled
 - Four (4) Duel Wheel Well Air Bottle Holders
 - Three (3) Adjustable Hose Bed Dividers
 - Assortment of Adjustable Shelves, Roll Out Trays, Vertical Pull Out Tool Boards
 - LED Strip Krystal Lite Compartment Lights
 - Vertical Ladder & Fold Da Tank Storage Through the Tank
 - 1000 Gallon Poly Tank
 - Floor Mount Console for Emergency Switches with Map Storage
 - Whelen Warning Light Package
 - Rub Rail LED Warning Lights & LED Ground Lights
 - Whelen Siren & Speaker
 - Two (2) Akron 12 V LED Lift Lights, One (1) Each Side
 - Whelen 12V 90 Series LED Scene Lights
 - Audiovox Back Up Camera with Cab & Pump Panel Monitors
 - Suction Storage Upper Body, One (1) Each Side
 - NFPA Chevron Rear Striping
 - 10' 1" Overall height
 - 36' Overall length
 - 293" Wheelbase
 - 180.5" Cab to Axle
 - 16,000 LB FAWR
 - 31,000 LB RAWR
 - 47,000 LB GVWR



To view more photos and download spec sheet, please visit us at AlexisFire.com.

