















- Cummins ISC330, 330-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- Stainless steel Body with Stainless Steel Sub-Frame and ROM Roll Up Doors
- Six (6) person cab seating with five (5) SCBA seats
- One (1) 2 1/2" Front bumper preconnect with center hose well
- 1250-Gallon Poly Tank
- One (1) 2 1/2" FirePrograms Tank fill, rear
- One (1) 10" square Newton Electric tank dump with 36" extension, rear
- Waterous CXS, 1250-GPM Pump with left side operator's panel
- Three (3) 2 ½" Discharges, two (2) left and one (1) right side
- Two (2) 3" Discharges, one (1) right side and one (1) over pump for deck gun One (1) 5" Front Suction and One (1) 2 ½" Gated Suction, left side
- One (1) 2 1/2" Mattydale Preconnect, across top of body
- Two (2) 1 ½" Cartridge Lay Preconnects, ahead of pump module
- One (1) Electric booster with 150-ft of 1" hose, pump module
- Three (3) Triple bottle Air bottle compartments, one (1) left and two (2) right
- One (1) Hinged pegboard swing out tool board, right side
- Ladder and Pike pole storage compartment right side with rear access
- Zico Hydraulic Folding Tank Rack for 2500-gallon tank, left side
- Suction Hose storage for two (2) hose on folding tank rack
- Turtle tile on floors and/or shelves and trays of compartments
- FireCom Intercom System
- One (1) Audiovox Back-up Camera system with 7" color monitor
- Federal Q2B mechanical Siren, pedestal mount front bumper
- 120 volt Electrical system utilizing customer supplied generator
- Command Knight 2, 12-volt Light Tower with four (4) Whelen LED lights
- Light Tower Guard
- FRC and Whelen Scene Light Packages
- Whelen LED Warning Light Package Diamond grade Chevron pattern striping, rear
- 10' 9" Overall height
- 18,000 FAWR • 27,000 RAWR
- 34' 4" Overall length 214" Wheelbase
- 45,000 GVWR
- 160" Cab to Axle















To view more photos and download spec sheet, please visit us at AlexisFire.com.

