











- Cummins L9, 450-HP Diesel Engine
- Allison 3000 EVS Automatic Transmission
- On Spot Automatic Tire Chains
- Heavy Duty Stainless Steel Body and Sub-Frame
- ROM Roll Up Doors

TECHNICAL SPECIFICATIONS

- Six (6) Person Cab Seating with Five (5) SCBA Seats Custom EMS Compartment, on Top of Doghouse
- 24" Front Bumper Extension with 11/2" Preconnect
- 1000-Gallon Poly Tank with 25 Gallon Foam Tank
- Waterous CX, 1500-GPM Pump with Left Side Control Operator's Panel
- Five (5) 21/2" Discharges, Two (2) Left, One (1) Right and Two (2) Rear
- Two (2) 3" Discharges, One (1) Right Side and One (1) Over Pump for Deck Gun
- Three (3) Mattydale Preconnects, Two 1½" and One 2½", Across Top of Body
- One (1) 2½" Gated Suction, Left Side
- One (1) Wheel Well Oil Dry Hopper, Right Side Two (2) Triple Bottle Air Bottle Storage Compartments, One (1) on Each Side
- Foam Pro 1600 Foam System
- Ziamatic Electrically Controlled Ladder Rack, Right Side
- One (1) Akron Hi Riser Monitor with Stream Shaper, Stacked Tips and Mounts
- Suction Hose Storage Area
- One (1) Audiovox Back-Up Camera System with 7" Color Monitor
- FireCom Wireless Intercom System
- PowerCall Electronic Siren with Two (2) PowerCall 100-Watt Speakers
- One (1) Nathan AriChime Train Air Horn Kit, Front Bumper
- Command Light Knight 2 Series Light Tower
- Whelen Split Arrow Stick
- Code 3 Warning Lights Package
- Akron Brass Scene Lights Package
- Diamond Grade Chevron Pattern Striping, Rear
- 10' 10" Overall height
- 32' Overall length
- 187" Wheelbase
- 133" Cab to Axle
- 20,000 FAWR
- 27.000 RAWR
- 47,000 GVWR













To view more photos and download spec sheet, please visit us at AlexisFire.com.

