

SIDE CONTROL EQUALIZER PUMPER #2558



TECHNICAL SPECIFICATIONS

- Spartan FC-94 MFD Chassis with 10" Raised Roof
- Cummins L9 450 HP Diesel Engine
- Allison 3000 EVS Transmission
- Heavy Duty Aluminum Body and Subframe
- Side Control Pump Module
- Hale DSD 1500 GPM Pump
- Trident 2-Location Air Primer
- FRC Pump Boss Max Pressure Governor Monitoring System
- FRC Tankvision Water Tank Level Gauge with Three (3) FRC MaxVision Strip Lites
- Two (2) 6" Intakes, One (1) Each Side
- One (1) 5" Front Intake with 6" Swivel Elbow
- One (1) 2½" Gated Intake, Left Side
- Two (2) 2½" Discharge, Left Side and One (1) 2½" Discharge, Right Side
- One (1) 3" Discharge Adapted to 5" Storz, Right Side
- One (1) 3" Discharge Adapted to 2½" MNST, Rear Right
- One (1) 3" Deck Gun Discharge in Dunnage Area with Elkhart Extender
- Two (2) 1½" and One (1) 2½" Crosslay Preconnects
- One (1) 1½" Bumper Extension Preconnect
- ROM Painted Roll-Up Doors
- Three (3) Dual Wheel Well Air Bottle Compartments
- Ladder Storage Horizontal in Rear Compartment with Two (2) Sections of Suction Hose
- 1000 Gallon Poly Tank with Hose Bed
- 12 Volt Electrical System with NFPA Compliant Warning Light Package
- Whelen LED Warning Light Package with Rear Arrow Stick
- Kussmaul Chief 4012 Battery Charger
- Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Left Side of Cab
- Whelen 200 Watt Siren and CPI 100 Watt Speaker
- Q2B Mechanical Siren
- Two (2) FireTech HiViz 8" LED Scene Light Bars, Rear
- One (1) FireTech HiViz 72" LED Brow Light
- Two (2) Whelen 9S LED Scene Lights, One (1) Each Side of the Cab
- Two (2) Akron Revel LED Telescopic Lights, One (1) Each Side of the Pump Module
- One (1) 10' Attic Ladder, One (1) 14' Roof Ladder with Hooks, One (1) 24' 2-Section Ladder, and Two (2) 10' Lengths of 6" Suction Hose
- 10'-2" Overall Height
- 31'10" Overall Length
- 180" Wheelbase
- 126" Cab to Axle
- 21,500 FAWR
- 31,500 RAWR
- 53,000 GVWR



