

## EQUALIZER PUMPER #2503



### TECHNICAL SPECIFICATIONS

- Spartan FC-94 MFD 10" Raised Roof
- Cummins L9 450 HP Engine
- Allison 3000 EVS Automatic Transmission
- Heavy Duty Stainless-Steel Body and Subframe
- 1000-Gallon Poly Tank
- Hale DSD 150 SS, 1500-GPM Split-Shaft Pump
- Side Control Pump Module with Enclosed Pump Panel L1/R1
- Two (2) 6" Intakes, One (1) Each Side
- One (1) 2 1/2" Gated Suction Left Side
- One 2 1/2" FirePrograms Rear Tank Fill
- Cartridge Lay Preconnects, Two (2) 1 1/2", One (1) 2 1/2"
- One (1) 24" Front Bumper Extension with 1 3/4" Front Bumper Discharge and Center Hose Well
- One (1) 2 1/2" Discharge Left Side
- One (1) 2 1/2" Discharge Right Side
- One (1) 3" Discharge with 5" Storz Adaptor, Right Side
- One (1) 3" Discharge adapted to 2 1/2" NST, Rear
- One (1) Akron 3423 Deck Gun with 18" TFT Extend-A-Gun
- ROM Painted Roll-Up Doors
- Three (3) Dual Bottle Wheel Well Compartments, One (1) Each side Ahead, Right side behind
- One (1) Vertical Pull Out Board, L1 Compartment
- Transverse Stokes Backboard Compartment, Above Cartridge Lays Ahead of Pump Module
- Ladder, Hard Suction, and Pike Pole Storage, Rear Access Through the Tank
- AFE Top Access Ladder
- Two (2) Hinged PacTrac Tool Board, L2 & R2 Compartments
- Two (2) 500# Roll-Out Trays, L3 Compartment & Rear Compartment
- One (1) Back-Up Camera with Cab Display
- Whelen Warning Light Package
- Whelen and FireTech Scene Lights
- Two (2) Fire Research Telescopic Scene Lights, One (1) Each side ahead of the Body
- Two (2) Air Horns Recess Bumper Mounted
- Whelen Electric Siren with 100W Speaker
- Kussmaul Battery Conditioner and Air Compressor with a Kussmaul 20-Amp 120V Super Auto-Eject Shoreline Inlet Left Side
- 9' 10" Overall Height
- 32' 8" Overall Length
- 182" Wheelbase
- 128" Cab to Axle
- 21,500 FAWR
- 31,500 RAWR
- 53,000 GVWR



