

3,000 GALLON TANKER #2628



TECHNICAL SPECIFICATIONS

- Freightliner M2 112 2-Door Chassis
- Cummins 450 HP L9 Engine
- Allison 3000 EVS Automatic Transmission
- Heavy Duty Stainless Steel Body and Stainless Steel Subframe
- Stainless Steel Intermediate Pump Module
- Hale DSD 1500 GPM Pump
- Trident Air Prime System
- FRC Pump Boss Max Pressure Governor
- FRC TankVision Water Tank Level Gauge with Three (3) FRC MaxVision Strip Lights
- Two (2) 6" Intakes, One (1) Each Side
- One (1) 2½" Gated Intake, Left Side
- Two (2) 2½" Discharges, Left Side and One (1) 2½" Discharge, Right Side
- One (1) 3" Discharge Adapted to 5" Storz, Right Side
- Two (2) 1½" and One (1) 2½" Crosslay Preconnects
- One (1) Booster Reel in R1 with 100' of 1" Booster Hose
- ROM Roll Up Doors
- Fol-Da-Tank Storage for 3000 Gallon Fol-Da-Tank, Right Side Compartment Top
- Suction Hose Storage, Left Side
- 3000 Gallon Poly Wetside Tank with Wetside Hose Bed & Front Fill Tower
- One (1) 4" FirePrograms Tank Fill with 4" Storz Elbow, Rear Left Side
- One (1) 10" Newton Stainless Steel Electric Swivel Dump with 36" Manual Extension, Rear
- 12 Volt Electrical System
- Progressive Dynamics Battery Charger with Viair Compressor, L1 Compartment
- Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Left Front Body Post
- Whelen LED Warning Light Package
- Whelen 200W Siren and 100W Speaker
- Federal Q2B
- Four (4) FireTech GESM Guardian Elite LED Scene Lights, One (1) Each Side and Two (2) Rear
- One (1) FireTech HiViz 21" LED Brow Light
- 9'-11" Overall Height
- 32'-8" Overall Length
- 236" Wheelbase
- 170.45" Cab to Axle
- 18,000 FAWR
- 44,000 RAWR
- 62,000 GVWR



